



Vehicle Care Products




BRITE AUTO CHERRY SPRAY SHINE

Clear coat protectant and sealer wax, scented with a pleasant cherry fragrance. **Cherry Spray Shine** can be used in friction and touchless conveyors and automatics as a menu upgrade. It can also be used in self-serves as a scented wax. **Cherry Spray Shine** provides shine and protection for all automotive finishes. It also beads water like a drying agent to enhance removal.

FEATURES & BENEFITS

- Produces a sparkling shine to paint finishes
- Pleasant cherry scent for customer appeal
- Provides water beading action to facilitate water removal from vehicle



APPLICATION

Product Use

Low pressure, low volume
High pressure, high volume

Recommended Application

1:128 to 1:256
1:256 to 1:512

Ounces per Gallon

1/2 to 1 oz./gallon
1/4 to 1/2 oz./gallon

DILUTE MANUALLY: 5 Gallons to 50 gallons of water, or through proportioners at 1:10 dilutions and apply at 2 1/2 to 10 ounces per car through spray arch, wand, or other delivery system.

NOTE: See reverse side for MSDS information and General Cautions for Use

Visit our website at www.ver-techlabs.com

MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Identity (As Used on Label and List): Brite Auto Cherry Spray Shine (EXT415)
Product Class: Drying Agent
Emergency Telephone Number: 800-535-5053 (INFOTRAC)
Telephone Number for Information: 763-509-7937
Manufacturer's Name and Address:
Ver-tech Labs
6801 Bleck Drive
Rockford, MN 55373

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components (Specific Chemical Identity):

Chemical	Common Name(s)
A	2-butoxy ethanol CAS #111-76-2
B	Quaternary Ammonium compounds CAS #61789-77-3
C	Mineral Seal Oil CAS #64742-46-7

SECTION III - HAZARDS IDENTIFICATION

Emergency Overview

Appearance and Odor: Red liquid, cherry/solvent odor.

Primary Hazards: Irritant

Potential Health Hazards

Route(s) of Entry: Skin Absorption: X Ingestion: X Inhalation: X

Eye: May cause Irritation

Skin: May cause Irritation

Ingestion: May be harmful if swallowed.

Inhalation: Overexposure to 2-Butoxy ethanol (butyl) / Mineral Seal Oil vapors may cause central nervous system effects including drowsiness, headaches, nausea and dizziness.

Signs and Symptoms of Exposure: Irritation on direct contact.

Carcinogenicity: NTP? No IARC Monographs? No

OSHA Regulated? No

Target Organ (s): Liver, kidneys, lymphoid system, skin, blood, eyes and respiratory system.

Medical Conditions Generally Aggravated by Exposure: N. Av.

Health Hazards, Chronic: Overexposure to 2-Butoxy ethanol (butyl) / Mineral Seal Oil may cause damage to one or more of the target organs listed above.

SECTION IV - FIRST AID MEASURES

Emergency and First Aid Procedures:

If Swallowed: Do not induce vomiting. Drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious person. **Eye Contact:** Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. **Skin Contact:** Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse.

Sources Used: Raw material data, general toxicology from the trade for similar products.

SECTION V - FIRE FIGHTING MEASURES

Flammability: N. Av. **Autoignition Temperature:** N. Av.

Flash Point (method used): None

Flammable Limits: N. Av. LEL UEL

Extinguishing Media: N. Av.

Water?	Foam?	Water Fog?
Alcohol Foam?	CO ₂ ?	Dry Chemical?
Vaporizing Liquid?	Other?	

Special Fire Fighting Procedures: N. Av.

Unusual Fire and Explosion Hazards: N. Av.

TDG Flammability Classification: Non-flammable

Sensitivity to Mechanical Impact: None

Sensitivity to Static Discharge: None

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be taken in Case Material is Released or Spilled:

Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop, absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area with water.

SECTION VII - HANDLING AND STORAGE

Precautions to be taken in Handling and Storing:

Normal care in handling and storage.

Other Precautions: Keep out of reach of children. Keep from freezing.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Types): Not required

Ventilation: Local Exhaust: Not required Special: Not required

Mechanical (General): Ventilate to keep vapor levels below PEL and TLV, listed in Section XI. **Other:** Not required

Protective Gloves: Natural rubber or synthetic.

Eye Protection: Approved safety goggles or glasses. **Footwear:** Chemical resistant

Other Protective Clothing or Equipment: Not required

Work/Hygienic Practices: Do not contaminate food or beverages with cleaning chemicals.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 212°F **pH:** 7 -10

Specific Gravity (H₂O) = 1: .9 -1.

Vapor Density (Air = 1): > N. Av. **Odor Threshold:** N. Av.

Evaporation Rate (Butyl Acetate = 1): N. Av. **Oil/Water Distribution**

Solubility in Water: Dispersible **Coefficient:** N. Av.

Vapor Pressure (MM HG): N. Av.

Melting Point: N. Av.

SECTION X - STABILITY AND REACTIVITY

Stability: Unstable: Stable: X

Conditions to Avoid: N. Av.

Incompatibility (materials to avoid): N. Av.

Hazardous Decomposition or By-products: N. Av.

Hazardous Polymerization: May occur: Will not occur: X

Conditions to Avoid: N. Av.

SECTION XI - TOXICOLOGICAL INFORMATION

Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
A	25 ppm (skin)	25 ppm (skin)	25 ppm	1.48 g/kg (rat, oral)	N. Av.
B	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.
C	5mg/m ³	N. Av.	N. Av.	5000mg/kg (rat,oral)	N. Av.

Teratogen, Mutagen, Reproductive Toxin Status: No known relevance to humans.

Toxicologically Synergistic Products: N. Av.

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicological Information: N. Av.

Chemical Fate Information: N. Av.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose of spilled material in accordance with local, state and federal regulations. Waste from normal cleaning procedures may be sewerred, depending on the materials and/or contaminants being cleaned as well as state, federal and local sewer commission regulations.

RCRA Hazard Class:

SECTION XIV - TRANSPORT INFORMATION

Shipping Classification: Cleaning Compound, n.o.s.

UN Number: N. Av.

Packing Group: N. Av.

SECTION XV - PREPARATION DATA

Prepared By: Health and Safety Department

Telephone Number: 763-509-7937

Date: 3-2-2009

SECTION XVI - REGULATORY INFORMATION

US Federal Regulations

TSCA Status: All ingredients listed.

CERCLA Reportable Quality: N. Av.

SARA Title III

Section 302 Extremely Hazardous Chemicals: None

Section 311/312 Hazard Category: Immediate health, chronic health.

Section 313 Toxic Chemicals: 2-butoxy ethanol (glycol ether),

SECTION XVII - OTHER INFORMATION

None

N. Av. - Not Applicable; N. Av. - Not Available

NFPA SYSTEM

2 A. Health Hazard 0 A. Fire Hazard 0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.