



Vehicle Care Products




# EVOLUTION

**Evolution** is a premium liquid drying agent. **Evolution** produces immediate water-beading action for fast drip-off and highest drying efficiency. **Evolution** can be used in friction and touchless automatics, conveyors and self service bays.

## FEATURES & BENEFITS

- **Fast beading**
- **Rapid stripping**
- **Shines as it dries**
- **Lowers labor costs**



## APPLICATION

**Product Use**  
All Applications

**Recommended Dilution**  
1:512 to 1:1000

**Usage per Car**  
1/8-1/4 oz. per gallon

Please note that dilution ratios may need to be adjusted based upon local conditions, such as pressure, water volume and arch volume.

NOTE: See reverse side for MSDS information and General Cautions for Use

Visit our website at [www.ver-techlabs.com](http://www.ver-techlabs.com)

# MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

<b>SECTION I - CHEMICAL PRODUCT &amp; COMPANY IDENTIFICATION</b>		
Identity (As Used on Label and List): Extreme Evolution Product Class: Drying Agent Emergency Telephone Number: 800-535-5053 (INFOTRAC) Telephone Number for Information: 763-509-7937 Manufacturer's Name and Address: Ver-tech Labs 6801 Bleck Drive Rockford, MN 55373		
<b>SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS</b>		
Hazardous Components (Specific Chemical Identity):		
Chemical	Common Name(s)	
A	2-butoxy ethanol CAS #111-76-2	
B	Mineral Seal Oil CAS #64742-46-7	
<b>SECTION III - HAZARDS IDENTIFICATION</b>		
Emergency Overview		
Appearance and Odor: Amber liquid, solvent odor. Primary Hazards: Irritant		
Potential Health Hazards		
Route(s) of Entry:	Skin Absorption: X Ingestion: X Inhalation: X	
Eye:	May cause Irritation	
Skin:	May cause Irritation	
Ingestion:	May be harmful if swallowed.	
Inhalation:	Overexposure to 2-Butoxy ethanol (butyl) / Mineral Seal Oil vapors may cause central nervous system effects including drowsiness, headaches, nausea and dizziness.	
Signs and Symptoms of Exposure:	Irritation on direct contact.	
Carcinogenicity:	NTP? No IARC Monographs? No	
OSHA Regulated?	No	
Target Organ (s):	Liver, kidneys, lymphoid system, skin, blood, eyes and respiratory system.	
Medical Conditions Generally Aggravated by Exposure:	N. Av.	
Health Hazards, Chronic:	Overexposure to 2-Butoxy ethanol (butyl) / Mineral Seal Oil may cause damage to one or more of the target organs listed above.	
<b>SECTION IV - FIRST AID MEASURES</b>		
Emergency and First Aid Procedures:		
If Swallowed: Do not induce vomiting. Drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious person. Eye Contact: Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. Skin Contact: Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse.		
Sources Used: Raw material data, general toxicology from the trade for similar products.		
<b>SECTION V - FIRE FIGHTING MEASURES</b>		
Flammability:	N. Av. Autoignition Temperature: N. Av.	
Flash Point (method used):	None	
Flammable Limits:	N. Av. LEL UEL	
Extinguishing Media	N. Av.	
Water?	Foam?	Water Fog?
Alcohol Foam?	CO <sub>2</sub> ?	Dry Chemical?
Vaporizing Liquid?	Other?	
Special Fire Fighting Procedures:	N. Av.	
Unusual Fire and Explosion Hazards:	N. Av.	
TDG Flammability Classification:	Non-flammable	
Sensitivity to Mechanical Impact:	None	
Sensitivity to Static Discharge:	None	
<b>SECTION VI - ACCIDENTAL RELEASE MEASURES</b>		
Steps to be taken in Case Material is Released or Spilled: Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop, absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area with water.		
<b>SECTION VII - HANDLING AND STORAGE</b>		
Precautions to be taken in Handling and Storing: Normal care in handling and storage. Other Precautions: Keep out of reach of children. Keep from freezing.		
<b>SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION</b>		
Respiratory Protection (Specify Types):	Not required	
Ventilation:	Local Exhaust: Not required Special: Not required	
Mechanical (General):	Ventilate to keep vapor levels below PEL and TLV, listed in Section XI. Other: Not required	
Protective Gloves:	Natural rubber or synthetic.	
Eye Protection:	Approved safety goggles or glasses. Footwear: Chemical resistant	
Other Protective Clothing or Equipment:	Not required	

Work/Hygienic Practices: Do not contaminate food or beverages with cleaning chemicals.					
<b>SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS</b>					
Boiling Point:	Approximately 212°F	pH:	7 -10		
Specific Gravity (H <sub>2</sub> O) = 1:	.9 -1.				
Vapor Density (Air = 1):	> N. Av.	Odor Threshold:	N. Av.		
Evaporation Rate (Butyl Acetate = 1):	N. Av.	Oil/Water Distribution			
Solubility in Water:	Dispersible	Coefficient:	N. Av.		
Vapor Pressure (MM HG):	N. Av.				
Melting Point:	N. Ap.				
<b>SECTION X - STABILITY AND REACTIVITY</b>					
Stability:	Unstable:	Stable:	X		
Conditions to Avoid:	N. Ap.				
Incompatibility (materials to avoid):	N. Av.				
Hazardous Decomposition or By-products:	N. Av.				
Hazardous Polymerization:	May occur:	Will not occur:	X		
Conditions to Avoid:	N. Ap.				
<b>SECTION XI - TOXICOLOGICAL INFORMATION</b>					
Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
A	25 ppm (skin)	25 ppm (skin)	25 ppm	1.48 g/kg (rat, oral)	N. Av.
B	5mg/m3.	N. Ap.	N. Ap.	5000 mg/kg (rat,oral)	N. Av.
Teratogen, Mutagen, Reproductive Toxin Status:		No known relevance to humans.			
Toxicologically Synergistic Products:		N. Av.			
<b>SECTION XII - ECOLOGICAL INFORMATION</b>					
Ecotoxicological Information:		N. Av.			
Chemical Fate Information:		N. Av.			
<b>SECTION XIII - DISPOSAL CONSIDERATIONS</b>					
Waste Disposal Method: Dispose of spilled material in accordance with local, state and federal regulations. Waste from normal cleaning procedures may be sewerred, depending on the materials and/or contaminates being cleaned as well as state, federal and local sewer commission regulations.					
RCRA Hazard Class:					
<b>SECTION XIV - TRANSPORT INFORMATION</b>					
Shipping Classification: Cleaning Compound, n.o.s.					
UN Number: N. Ap.					
Packing Group: N. Ap.					
<b>SECTION XV - PREPARATION DATA</b>					
Prepared By: Health and Safety Department					
Telephone Number: 763-509-7937					
Date: 6-26-2008					
<b>SECTION XVI - REGULATORY INFORMATION</b>					
US Federal Regulations					
TSCA Status: All ingredients listed.					
CERCLA Reportable Quality: N. Av.					
SARA Title III					
Section 302 Extremely Hazardous Chemicals: None					
Section 311/312 Hazard Category: Immediate health, chronic health.					
Section 313 Toxic Chemicals: 2-butoxy ethanol (glycol ether),					
<b>SECTION XVII - OTHER INFORMATION</b>					
None					
N. Ap. - Not Applicable; N.Av. - Not Available					

## NFPA SYSTEM

2 A. Health Hazard      0 A. Fire Hazard      0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.