



Vehicle Care Products



PRESOAK PRO II

Presoak Pro II is a highly versatile low pH detergent that can be used as a low pressure presoak, high or low pressure detergent, or as the first step in a two step low pH/high pH wash process. This product loosens road film and heavy residue soils that can not be removed by ordinary spray cleaning. **Presoak Pro II** is our best selling liquid presoak for frictionless in-bay automatics.

FEATURES & BENEFITS

- **Fast acting on all soils to minimize time and labor costs**
- **Removes heavy road film, soot, and oil to increase effectiveness of the cleaning process**
- **High foaming**
- **Ideal for cleaning windows and brightening chrome**
- **Designed for use in in-bay automatics with high pressure equipment**
- **Fully biodegradable**

APPLICATION

Heavy soiled surfaces should be pre-cleaned before using this product. Rinse well, do not combine this product with any alkaline products.

*****CONSULT A TRAINED SALES REPRESENTATIVE FOR OTHER USES*****

DILUTION RATIOS

<u>Product Use</u>	<u>Recommended Application</u>	<u>Ounces per Vehicle</u>
Presoak	60:1 to 150:1	.75 to 1.5

NOTE: See reverse side for MSDS information and General Cautions for Use

Visit our website at www.ver-techlabs.com

MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Identity (As Used on Label and List): Presoak Pro II (EXT115)

Product Class: Low pH Car Wash Presoak

Emergency Telephone Number: 800-535-5053 (INFO TRAC)

Telephone Number for Information: 763-509-7937

Manufacturer's Name and Address:

Ver-tech Labs
6801 Bleck Drive
Rockford, MN 55373

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components (Specific Chemical Identity):

Chemical	Common Name(s)
A	Aliphatic Hydrocarbon CAS #64742-47-8
B	2-butoxy ethanol CAS #111-76-2
C	Hydrofluoric acid (HF) CAS #7664-39-3

SECTION III - HAZARDS IDENTIFICATION

Emergency Overview

Appearance and Odor: Amber liquid, mild aroma.

Primary Hazards: Corrosive Toxic

Potential Health Hazards

Route(s) of Entry: Skin Absorption: X Ingestion: X Inhalation: X

Eye: Causes severe chemical burns if contact occurs.

Skin: Causes severe chemical burns if contact occurs.

Ingestion: Harmful or fatal if swallowed.

Inhalation: Overexposure to vapors harmful.

Signs and Symptoms of Exposure: Irritation and/or burning sensation on contact can be delayed up to 24 hours. Vapors may cause central nervous system effects

Carcinogenicity: NTP? No IARC Monographs? No

OSHA Regulated? No

Target Organ (s): liver kidneys lymphoid system skin blood eyes and respiratory system

Medical Conditions Generally Aggravated by Exposure: N. Av.

Health Hazards, Chronic: Fluoride poisoning.

SECTION IV - FIRST AID MEASURES

Emergency and First Aid Procedures: Treat for Fluoride Poisoning.

If Swallowed: Do not induce vomiting. Rinse mouth and drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious person. **Eye Contact:** Flush eyes with running water for at least 15 minutes. Obtain immediate medical attention. **Skin Contact:** Flush thoroughly with cool water. Remove contaminated clothing and apply calcium gluconate gel. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

Sources Used: Raw material data, general toxicology from the trade for similar products.

SECTION V - FIRE FIGHTING MEASURES

Flammability: N. Av. **Autoignition Temperature:** N. Av.

Flash Point (method used): N. Av.

Flammable Limits: N. Av. LEL UEL

Extinguishing Media

Water?	Foam?	Water Fog?	X
Alcohol Foam? X	CO ₂ ? X	Dry Chemical?	X
Vaporizing Liquid? X	Other?		

Special Fire Fighting Procedures: High heat will release acidic vapors.

Unusual Fire and Explosion Hazards: N. Av.

TDG Flammability Classification: N. Av.

Sensitivity to Mechanical Impact: None

Sensitivity to Static Discharge: t.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be taken in Case Material is Released or Spilled:

Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop, absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area with water.

SECTION VII - HANDLING AND STORAGE

Precautions to be taken in Handling and Storing:

Normal care in handling and storage. Do not store near heat or open flame.

Other Precautions: Keep out of reach of children. Do not breathe spray mist.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Types): Not normally required.

Ventilation: Local Exhaust: Not required **Special:** Not required

Mechanical (General): Provide ventilation adequate to disperse cleaner vapors and or mists. **Other:** Not required

Protective Gloves: Synthetic.

Eye Protection: Approved safety goggles or glasses. **Footwear:** Chemical resistant

Other Protective Clothing or Equipment: Chemical resistant

Work/Hygienic Practices: Do not contaminate food or beverages with chemicals.

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 212°F

pH: 1 - 2

Specific Gravity (H₂O) = 1: 1 - 1.04

% Volatile:

Vapor Density (Air = 1): N. Av.

Odor Threshold: N. Av.

Evaporation Rate (Butyl Acetate = 1): N. Av.

Oil/Water Distribution Coefficient: N. Av.

Solubility in Water: Complete

Melting Point: N. Ap.

Vapor Pressure (MM HG): N. Av.

SECTION X - STABILITY AND REACTIVITY

Stability: Unstable: Stable: X

Conditions to Avoid: Mix only with water

Incompatibility (materials to avoid): Metals, Alkaline materials

Hazardous Decomposition or By-products: N. Av.

Hazardous Polymerization: May occur: Will not occur: X

Conditions to Avoid: N. Ap.

SECTION XI - TOXICOLOGICAL INFORMATION

Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
----------	----------	-----------	--------	------	------

A	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.
---	--------	--------	--------	--------	--------

B	25 ppm skin	25 ppm skin	N. Av.	1.48 mg/kg (rat, oral)	N. Av.
---	-------------	-------------	--------	------------------------	--------

C	3 ppm	3ppm	N. Av.	N. Av.	N. Av.
---	-------	------	--------	--------	--------

Teratogen, Mutagen, Reproductive Toxin Status: No

Toxicologically Synergistic Products: N. Av.

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicological Information: N. Av.

Chemical Fate Information: N. Av.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose of spilled material in accordance with local, state, and federal regulations.

RCRA Hazard Class: D002 Corrosive

SECTION XIV - TRANSPORT INFORMATION

Shipping Classification: Corrosive liquid, toxic, n.o.s., (Hydrofluoric Acid), 8, (6.1)

UN Number: 2922

Packing Group: II

SECTION XV - PREPARATION DATA

Prepared By: Health and Safety Department

Telephone Number: 763-509-7937

Date: 8-5-2010

SECTION XVI - REGULATORY INFORMATION

US Federal Regulations

TSCA Status: All ingredients listed.

CERCLA Reportable Quality: N. Av.

SARA Title III

Section 302 Extremely Hazardous Chemicals: Hydrogen fluoride

Section 311/312 Hazard Category: Immediate health hazard

Section 313 Toxic Chemicals: Hydrogen Fluoride, 2 butoxy ethanol (Glycol ether)

SECTION XVII - OTHER INFORMATION

N. Ap. - Not Applicable; N. Av. - Not Available

NFPA SYSTEM

3 A. Health Hazard 1 A. Fire Hazard 0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THERE OF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.